




# How to recommend the most appropriate Ground-Guards

## STEP 1: ASK THE FOLLOWING QUESTIONS

1. What's the desired length and width of the trackway or pad area?
2. How heavy / What type of vehicles will be using the trackway?
3. What are the ground conditions like?
4. How long will the trackway or pad area be needed for?

## STEP 2: USE YOUR QUESTIONS 2, 3 AND 4 ABOVE TO DETERMINE CHOSEN PRODUCT

	MultiTrack	MaxiTrack	LiteTrack
Light 	✓		✓
Medium 	✓	✓	
Heavy 	✓	✓	
Firm/Dry ground	✓	✓	✓
Soft/Damp ground		✓	
Low traffic (less than 6 vehicles per day for less than 4 weeks)	✓		✓
High traffic (more than 6 vehicles per day for more than 4 weeks)	✓	✓	

## STEP 3: DETERMINE TRACKWAY TYPE

- If MultiTrack <2 weeks = Recommend twin trackway
- If MultiTrack >2 weeks = Recommend solid trackway
- If MaxiTrack = Always use solid trackway

## PLEASE NOTE

If the weather turns wet you may need to increase your level of ground protection.

If steel tracked excavators are being used, please consult Ground-Guards for further advice.

## STEP 4: FINAL QUESTIONS:

- Are there any delivery restraints?
- Is off-loading available?
- Are there any restrictions on size of vehicles?
- When is it required for?